

Profilo scanalato alveolare – INO003-F

Features

Elastico e resistente al peso, all'impatto alla trazione e resiste alle deformazioni e rotture; resistente agli sbalzi di temperatura ed ai raggi solari; resistente ai raggi ultravioletti ed agli agenti chimici; lavabile, resistente e stabile a contatto con l'acqua; inattaccabile dagli agenti atmosferici; atossico ed ecologico; autoestinguente di facile utilizzo; aspetto versatile a seconda delle esigenze e delle richieste; non si scheggia e non si fessura; durevole; riciclabile all'infinito. Il WPC è un legno composito pertanto si presta alle varie lavorazioni come fosse legno e di conseguenza si possono utilizzare le stesse attrezzature, può essere tagliato, fresato, contornato, levigato, si possono inserire inserti, rivetti, e viti. Oltre alle misure standard, sono disponibili altre misure su richiesta specifica del cliente, senza maggiorazioni di prezzi. **NON HA BISOGNO DI MANUTENZIONE**

.....

Dimension

143 mm x 28 mm. peso: 3,10 Kgm.

.....

Product informations

Commercial name: Profilo scanalato alveolare - INO003-F

Material: PVC

Recycled total	Post-consumer recycled	Pre-consumer recycled	By-product total	External by-product	Internal by-product	Virgin material
91%	--	91%	--	--	--	9%

Productor informations

INOCRAM SRL

VIA DELLE INDUSTRIE, 58/1, PAVIA DI UDINE, Udine, Friuli-Venezia-Giulia, Italia

Telephone: 0432 675494

Mail: info@inocram.it

Website: www.inocram.it

June 19, 2025