Isolamento termico – Sicuro Green K150



Features

Pannello termoisolante in polistirene espanso sinterizzato di colore verde puntinato realizzato con le migliori materie prime italiane. È consigliato per la realizzazione dell'isolamento termico dove è richiesta alta resistenza meccanica e basso assorbimento d'acqua come nelle zoccolature murarie. Il pannello è indicato in applicazioni dove è richiesta un'elevata resistenza meccanica. Colore: grigio/verde

Dimension

lunghezza: 2000 mm ÷ 100 mm. Larghezza: 1500 mm ÷ 100 mm. Spessore: 1000 mm ÷ 20 mm Conducibilità termica: W/mK ≥ 0,033 Resistenza alla compressione al 10% di deformazione kPa ≥ 150

Product informations

Commercial name: Isolamento termico - Sicuro Green K150
Material: EPS
PSV MixEco

Waste type	Waste origin	Recycled total	Post-consumer recycled	Pre-consumer recycled	By-product total	External by-product	Internal by-product	Virgin material
--	--	15%	15%	--	--	--	--	85%

Productor informations

POLISETTE SRL
VIA SAN VITALE, 15, SALA BAGANZA, Parma, Emilia Romagna, Italia
Telephone: 0521 833694
Mail: andrea.azzali@teampolisette.com
Website: https://www.polisette.it/

November 12, 2024